



Aritco 7000 Platform Lift



Aritco 7000 - our bestselling platform lift

The lift is designed to meet all requirements for quality, safety and service life. It is a perfect fit for tough and demanding environments such as schools, shops and residential buildings.

Several advantages offered by Aritco 7000:

- Design, sizes and options tailored to public environments
- 95% recyclable materials
- 'A' rated energy consumption according to VDI4707
- Patented screw/nut technology (no oil that can leak)
- The lowest maintenance and operating costs on the market





ARITCO™

Aritco 7000 Platform Lift




Length

Width




900 x 1040

Hole through floor: 1330x1190 mm
(No door on B-side: 1305x1190)
Platform: 900x1040 mm
Load: 250 kg
Wheelchair: -




900 x 1280

Hole through floor: 1330x1430 mm
(No door on B-side: 1305x1430)
Platform: 900x1280 mm
Load: 410 kg
Wheelchair: Lone user or type A*




900 x 1480

Hole through floor: 1330x1630 mm
(No door on B-side: 1305x1630)
Platform: 900x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant*




1000 x 1280

Hole through floor: 1430x1430 mm
(No door on B-side: 1405x1430)
Platform: 1000x1280 mm
Load: 410 kg
Wheelchair: Lone user or type A*




1000 x 1480

Hole through floor: 1430x1630 mm
(No door on B-side: 1405x1630)
Platform: 1000x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant*




1000 x 1980

Hole through floor: 1430x2130 mm
(No door on B-side: 1405x2130)
Platform: 1000x1980 mm
Load: 500 kg
Wheelchair: A or B with attendant*



1100 x 1480

Hole through floor: 1530x1630 mm
(No door on B-side: 1505x1630)
Platform: 1100x1480 mm
Load: 410, 500 kg
Wheelchair: A or B with attendant, adjacent entry*



1100 x 1580

Hole through floor: 1530x1730 mm
(No door on B-side: 1505x1730)
Platform: 1100x1580 mm
Load: 500 kg
Wheelchair: A or B with attendant, adjacent entry*

Wheelchair Type A and B according to EN 12183/EN 12184.
* National guidelines may apply.

Dimensions

Platform width 900-1100 mm
Platform length ... 1040-1980 mm
Travel height 250-13000 mm

Hole through floor width.... 1305-1530 mm
Hole through floor length .. 1190-2130 mm
Top height 2240 mm

Height of door opening¹⁾.. 1800, 1900, 2000, 2100 mm
Height of door opening²⁾..... 1100-1600 mm
Width of door opening 800, 900, 1000 mm

1) Full-height door 2) Half-height door

Specifications

Drive system: Patented screw/nut system

Rated speed: max 0.15 m/s

Platform control: "Hold to run", the button has to be kept pressed during the ride

Landing control: One-touch call

Technical compliance:
European Machinery Directive 2006/42/EC
European standard EN 81-41

Rated load: 250-500 kg / 2-5 persons

Number of stops: max 6

Number of doors: max 2 doors per floor

Pit: 50 mm (no pit is required when there is a ramp)

Environment: Indoors and outdoors

Power supply:
1-phase 230V 50Hz/9A/16A slow
3-phase 230V 50Hz/9A/16A slow
3-phase 400V 50Hz/5.2A/16A slow

Emergency lowering: Battery-powered

Control voltage: 24V

Motor: 2.2 kW

For more information, please, refer to our product catalogue or visit our website.

Due to the continuous product development at the company, the information may change without prior notice.